

Compa V

High versatility in a brand new look.



Highlights

- > Large label rolls with a diameter up to 205 mm
- > Print speed up to 300 mm/s
- > Easy to operate and maintain
- > Graphic display with white background lighting
- > Serial, LAN and USB port
- > Slot for SD card
- > Stand-alone mode
- > Double sensor system

Options

- > Rotation cutter unit
- > Dispenser unit
- > Dispenser/O
- > Internal rewinder
- > External label rewinder
- > Pneumatic applicator

Guillotine cutter unit



Dispenser unit



External label rewinder



WILUX PRINT AG
Unterfeldstrasse 5
CH-8340 Hinwil

Tel.: +41 (0)55 253 24 24
Fax: +41 (0)55 253 24 25

mail@wilux.ch
www.wilux.ch
www.labellingshop.com



wilux print
swissness
Ihr Partner für Etikettier- und Kennzeichnungslösungen

	Compa V 103/8	Compa V 104/8	Compa V 106/12	Compa V 106/24	Compa V 108/12	Compa V 162/12
Printing						
Print resolution	203 dpi	203 dpi	300 dpi	600 dpi	300 dpi	300 dpi
Print speed (max)	300mm/s	300mm/s	300mm/s	150mm/s	300mm/s	250mm/s
Print width (max)	104 mm	104 mm	105.7 mm	105.6 mm	108.4 mm	162.6 mm
Passagewidth (max)	120 mm	120 mm	120 mm	120 mm	120 mm	180 mm
Printing principle	TT/TD ¹	TT ²	TT ²	TT ²	TT/TD ¹	TT/TD ¹
Labels						
Labels, continuous rolls or fan-fold	paper, cardboard, textile, synthetics					
Material weight (max)	max. 220 g/m ² (larger on demand)					
Labelwidth (min)	20 mm					46 mm
Linerwidth (min)	25 mm					50 mm
Labelheight (min) Standard Cutter/dispenser mode	5 mm 15 mm					5 mm 25 mm
Label height (max) Standard Dispenser mode	6000 mm 200 mm	6000 mm 200 mm	3000 mm 200 mm	750 mm 200 mm	3000 mm 200 mm	2000 mm 200 mm
Roll diameter (max)	205 mm					
Core diameter Standard Additional dimensions	Ø 40 mm Ø 38.1 up to Ø 76 mm (optional additional cores possible)					
Winding	outside or inside					
Label sensor	transmission and reflexion from below					
Transfer ribbon						
Ink	outside or inside					
Core diameter	25.4 mm / 1"					
Roll diameter (max)	Ø 90 mm					
Length (max)	600 m					
Width (max)	114 mm					170 mm
Internal rewriter for printers						
Outside diameter	142 mm					
Core diameter	Ø 40 mm					
Winding	outside					
Fontsand bar codes						
Font types	6 bitmap Fonts 8 vector fonts/TrueType fonts 6 proportional fonts other fonts on demand					
1D bar codes	CODABAR, Code 128, Code 2/5 interleaved, Code 39, Code 39 extended, Code 93, EAN 13, EAN8, EANADD ON, GS1-128, Identcode, ITF 14, Leitcode, Pharmacode, PZN7 Code, PZN8 Code, UPC-A, UPC-E					
2D bar codes	Aztec Code, CODABLOCKF, DataMatrix, GS1DataMatrix, MAXICODE, PDF417, QRCode					
GS1 bar codes	GS1DataBar Expanded, GS1DataBar Limited, GS1DataBar Omnidirectional, GS1DataBar Stacked, GS1DataBar Stacked Omnidirectional, GS1DataBar Truncated					
Dimensions						
Width x height x depth (mm)	252 x 288 x 460					312 x 288 x 460
Weight	10 kg					14 kg
Interfaces						
Serial	RS-232C (bis 115.200 Baud)					
USB	2.0 High Speed Slave					
Ethernet	10/100 BaseT, LPD, RawIP-Printing, DHCP					
2 x USB Host	on the back for: keyboard, USB memory stick					
Operating data						
Powersupply	110 ... 240VAC/50-60 Hz					
Max. power consumption	200 VA					
Nominal current	2.5 A					
Operating temperature	5 ... 35 °C					
Relative humidity	max. 85 % (non-condensing)					

¹ = Thermaltransfer/thermal direct . ² = Thermaltransfer

WILUX PRINT AG
Unterfeldstrasse 5
CH-8340 Hinwil

Tel.: +41 (0)55 253 24 24
Fax: +41 (0)55 253 24 25

mail@wilux.ch
www.wilux.ch
www.labellingshop.com

